


THE TOUR CONTRACTOR OF THE PROPERTY OF THE PRO

**-6-**

["

P )
P P
P
P
RES
P 3.0/R
P 3.1/T
P 3.2/T
P 3.3/I
P 3.6,
P 3.7
X'I


## 6. [CPU-09] PRINTED CIRCUIT BOARD



Q1 02~5 Q6	2SA664R 2SA874R 2SC3331T	802362 902508
[ Oiode ]		


D1	OSK-108	802898
D2	MA-700	802364
D3	LT8001P	802940
1		


TLP552



MSM74HC04 कें के के के के के

MSM74HC02






4 3 0 1 9 0 0 + + SW-61/PS-41 **≪** D > ≪C>


MSM74HC374

V<sub>PO</sub> Q, D. D. Q. Q. O. D. Q. CLOC 20 19 18 17 16 15 14 11 12 11 1 2 1 4 5 6 7 5 9 100 OUTPUT Q, D, D, Q, Q, D. O, Q V.,


MSM74HC174




74LS00



74ALS374



74LS161



SW-146

< A >

∢B≯


**–** 8 –

m N -


≪B≫


22 k 22 k 012 25C3331T


## 8. [SYN-61] PRINTED CIRCUIT BOARD




The state of the s









## 12. [FH-14], [PS-41], [JA-20], [SW-146] PRINTED CIRCUIT BOARD






$\rightarrow$	Description	Japan	General	U.S.A.	Canada	NE
1	Fuse	1.0A	1.0A	1.0A-250V	1.0A-250V	NE
2	Fuse	0.8A	0.8A			T-1.0A
3	Fuse	0.8A	0.8A		0.8A-250V	T-0,8A
4	Power Transformer		0.8A		0.8A-250V	T-0.8A
5	Fuse			TSE-246-U		
3	Fuse	0.54	0.5A			T-0.5A
,		0.5A	0.5A	0.5A-250V	0.5A-250V	T-0.5A
	AC Cord					
3~9	Capacitor	DEFZ103PVAI-KC	DE7150FZ103PVAI-KC	DE7150F7103PVI-KC	DE7150E7102BVI KC	DE7150571000VI




[ IC ]			
IC No.	Name	Code No.	Abstract
IC1 IC2 IC3	AN7805F AN7815F AN7915F	802888 802889 802890	Positive Voltage Regulator Positive Voltage Regulator Negative Voltage Regulator


[ Diode ]			
D1, 2 D3, 4	DSK10B RB-152	802898 706319	
<u> </u>			

## 13. TROUBLESHOOTING GUIDE



SECTION OF THE PROPERTY OF THE





12 (39 ) STOREST TARROW, (SW. 460) PRIME SOUTH FOR A STOREST